



12 SERIES



OIL FIRED PORTABLE PRESSURE WASHER | Specifications:

GENERAL						ELECTRICAL			BURNER SYSTEM		DIMENSIONS/WEIGHT			
Model	Type	GPM	PSI	HP	Drive	Volt	Amp	Ph	BTU	Stack Size	L	W	H	Lb
12-203D	ED	2	300	.75	Direct	115	20	1	179,000	8"	31.5"	24.5"	39"	290
12-212	ED	2	1200	2	Direct	120	20	1	175,000	7"	31.5"	24.5"	39"	300
12-320D	ED	3	2000	4	Direct	230	20	1	269,000	7"	31.5"	24.5"	39"	320
12-303D	ED	3	300	.75	Direct	115	15	1	383,000	8"	37.5"	29"	44.5"	380
12-210CD	ED	2.2	300/1000	1.5	Direct	115	20	1	383,000	8"	37.5"	29"	44.5"	415
12-216	ES/EL	2	1600	2.3	Belt	120	20	1	175,000	7"	31.5"	24.5"	39"	310
12-310	ES/EL	3	1000	2.3	Belt	115	20	1	269,000	7"	31.5"	24.5"	39"	310
12-325	ES/EL	3	2500	5	Belt	230	20	1	269,000	7"	31.5"	24.5"	39"	325
12-423	ES/EL	4	2300	6	Belt	230	30	1	384,000	8"	37.5"	29"	44.5"	465
12-430	ES/EL	4	3000	8	Belt	230	40	1	384,000	8"	37.5"	29"	44.5"	485

Features (not shown on breakout):

ED Model Features:

- Heavy Duty Electro Plated Fittings
- Built-In Hose Reel Socket
- 3/8" x 40' High Pressure Hose
- Four Wheel Design
- ASTM A53 Schedule 80 Steel Heating Coil
- Fuel Oil Solenoid
- In-Line Fuel Filter
- Trigger Gun Control
- 36" Insulated Wand

- Flood Nozzle w/Fixed 15° Spray Tip
- GFCI Protection w/10' Electrical Cord

ES - Includes All the Features of ED Plus:

- Belt Driven Pump
- Exclusive High Strength Nylon Manifold
- Quick Couple Manifold Plumbing Connections
- Polyethylene Fuel Tank w/Chemical Metering
- 0° & 15° Quick Couple Nozzles

EL - Includes All the Features of ED Plus:

- Stainless Steel Belt Guard & Wrapper
- Stainless Steel Electrical Control Panel
- Water Separating Fuel Filter
- 3/8" x 50' High Pressure Hose
- GFCI Protection w/36' Electrical cord (except 12-430)
- In-Line Fuel Shutoff
- Accessory Package



A Closer Look at the Features:



Notes:

Configured for you by:

HYDRO-SPRAY

2928 Washington Ave • Clearfield, PA 16830
1-800-664-5697 • info@hsws.net
www.hydro-spray.net