



500 SERIES



COLD WATER PRESSURE WASHER | Specifications:

GENERAL										
Model	GPM	PSI	HP	Drive	Pump	Engine	Engine Fuel	Nozzle	Hose	Weight
532.4-RES	2.8	2400	5	Direct	Axial Radial	Honda	Gas	15°, 40°, Soap	3/8" x 30'	95
532.5-G	3	2500	6.5	Direct	Triplex Plunger	Honda	Gas	0°, 15°, 40°, Soap	3/8" x 30'	105
544-G	4	4000	13	Direct	Triplex Plunger	Honda	Gas	0°, 15°, 40°, Soap	3/8" x 50'	160
544-GBD	4	4000	13	Belt	Triplex Plunger	Honda	Gas	0°, 15°, 40°, Soap	3/8" x 50'	246
530-BDC	5	3000	16	Clutch	Triplex Plunger	Vanguard	Gas	0°, 15°, 40°, Soap	3/8" x 40'	100
533.5-V	3	3500	10	Direct	Triplex Plunger	Vanguard	Gas	0°, 15°, 40°, Soap	3/8" x 40'	170
544-V	4	4000	16	Direct	Triplex Plunger	Vanguard	Gas	0°, 15°, 40°, Soap	3/8" x 40'	180

Features:

- Heavy Duty Gas Engine
- Durable Powder Coat Frame
- Pneumatic Tires
- 0°, 15°, 40° & Soap Quick Couple Nozzles (except 532.4-RES)
- Extended Handle for Easy Mobility
- Hose & Gun Hangers
- Heavy Duty Ceramic Plunger Triplex or Axial Pump
- High Pressure Hose & Gun Assembly
- Unloader Valve
- Belt or Direct Drive
- Low Pressure Chemical Injection

A Closer Look at the Features:



Notes:

Configured for you by:

HYDRO-SPRAY
WASH SYSTEMS, INC.

2928 Washington Ave • Clearfield, PA 16830
1-800-664-5697 • info@hsws.net
www.hydro-spray.net